



6/12 DAZ 005

# EXPANSION UNIT

## WITH 3 OR 6 ROCKER SWITCHES

The expansion unit provides three or six momentary rocker switches for the expansion of the digital outdoor intercom stations of the DA/DAE series. Connect up to five expansion units to one digital outdoor intercom station.



- Robust expansion unit for use in harsh industrial environments
- Degree of protection IP66
- Housing made of glass-fiber reinforced polyester
- Up to 6 momentary rocker switches
- Designed for use with industrial gloves
- Visual call or busy status via LED
- Modular design for easy maintenance

### COMPONENTS

- Two-part glass-fiber reinforced polyester housing, hardly inflammable
- Basic housing with connection board
- Up to 6 momentary rocker switches of the 2 HDX 04 series with signaling LEDs and labeling field
- 6 DSZ 05 electronics unit


### MECHANICAL DATA

<b>Width x height x depth</b>	141 mm x 484 mm x 171 mm (5.55" x 19.06" x 6.73")
<b>Cable glands</b>	2 x M20 (cable diameter: 5 mm to 13 mm (0.20" to 0.51"))
<b>Connection</b>	Cable cross-section Solid: 0.2 mm <sup>2</sup> to 4 mm <sup>2</sup> (24-12 AWG) Flexible stranded: 0.2 mm <sup>2</sup> to 2.5 mm <sup>2</sup> (24-14 AWG)
<b>Weight</b>	Approx. 4 kg (8.82 lbs)
<b>Color</b>	Pure Orange (RAL 2004)

### ELECTRICAL DATA

<b>Operating voltage</b>	42 V DC to 68 V DC
<b>Max. current consumption</b>	20 mA

## DIMENSIONS



## ENVIRONMENTAL REQUIREMENTS AND STANDARDS

<b>Ambient temperature during operation</b>	-40 °C to +70 °C (-40 °F to +158 °F)
<b>Relative humidity (non-condensing)</b>	Max. 95%
<b>Degree of protection</b>	IP66
<b>EMC</b>	IEC / EN 61000-6-2 IEC / EN 61000-6-4

## ORDER DATA

No. Rocker Switches	Type	Type Number
3	6 DAZ 005	301-414-000*
6	12 DAZ 005	301-414-200*

\*Expansion unit can also be ordered in red (RAL 3000) on request.

© INDUSTRIONIC