

9 ZSW 02

WALL-MOUNTED CABINET

WITH 9 RU AND GLAZED DOOR

The wall-mounted cabinet 9 ZSW 02 with 9 RU and glazed front door is used to accommodate INDUSTRONIC system components. It consists of solid sheet-steel panels. The glazed front door is hinged on the left. The door handle can be equipped with an optional safety lock. The electronics is mounted into the 19" swing frame. The connections for the installation cables are located on the rear panel. Cable entry is done by means of cable glands in removable flange plated on top or bottom side of the cabinet. Optionally, active and passive ventilation systems are available for cooling.



- Glazed front door with safety glass
- 19" swing frame with 9 RU
- Door hinge at the left
- Swing frame hinge at the left
- Cable entry on top or bottom side
- Wall-mounting bracket

MECHANICAL DATA

| | |
|---|--|
| Housing | Sheet steel |
| Glazed door at the front | Extruded aluminum with safety glass |
| Width x height x depth | 600 mm x 478 mm x 472.5 mm (23.62" x 18.82" x 18.60") |
| Curb weight | 35 kg (77.16 lbs) |
| Main color | Light gray (RAL 7035) |
| Degree of protection* | IP55 acc. to EN 60529 |
| Sheet steel thickness of panels | 1.5 mm (0.06") |
| Paint thickness | 60 µm to 120 µm (2.36 mil to 4.72 mil) |
| Swing frame | 19", 9 RU |
| Static load of swing frame | Max. 45 kg (99.12 lbs) |
| Door opening angle | 120° |
| Door hinge | left |
| Swing frame hinge | left |
| Ambient temperature during operation | 0 °C to +40 °C (+32 °F to +104 °F) |

*The degree of protection is only valid if the outer cabinet enclosure has not been modified. Additional openings or attachments (e.g. ventilation equipment, flashing warning beacons, etc.) on the outer enclosure may result in a lower degree of protection.

ORDER DATA

Type number 225-470-000

© INDUSTRONIC